

OVERHEAD DOOR

ASSA ABLOY

971 H LAVAL CRES.
KAMLOOPS, BC V2C 5P4

PHONE: (250) 374-5655
FAX: (250) 828-1054

DATE: Dec 1, 2017

PROJECT: village walk at sunpeaks

SECTION: div 8 overhead doors and operators.

GUARANTEE:

ALL MATERIALS ARE GUARANTEED FROM ANY DEFECTS FROM THE USE OF MATERIALS, DEFICIENCIES OF DESIGN STRENGTH OR BY REASON OF POOR WORKMANSHIP WHICH MAY APPEAR WITHIN 1 YEAR(S) FROM THE DATE OF SUBSTANTIAL PERFORMANCE.

ASSA ABLOY ENTRANCE SYSTEMS



DAN VALIQUETTE

8355

1/2 HP AC BELT DRIVE GARAGE DOOR OPENER



Smart, Quiet and Energy Efficient

Connectivity

- **MyQ® Technology** enables you to securely monitor and control your garage door opener and houselights with your smartphone, tablet or computer. (Requires purchase of Internet Gateway (828LM)).
- **Alerts** can be received as email or pop-up (push) notifications on your mobile device so that you always know the status of your garage door and houselights.
- **MyQ mobile app** is a free download requiring no annual activation fee.

Performance

- **P3™ Motors** are reliable, durable and powerful – designed specifically for your needs.
- **1/2 HP AC motor** with industrial strength belt drive system provides quiet, reliable and maintenance free performance.
- **Motor Vibration Isolation System (MVIS®)** provides super quiet, smooth operation year after year.
- **Energy-efficient** operation consumes up to 75% less power in standby mode.
- **Lifetime motor** and belt warranty. 1-year parts warranty.

Safety and Security

- **Security+ 2.0®** safeguards your household – with every click a new code is sent to the garage door opener so that the door opens only for you.
- **PosiLock®** locks down your door by electronically monitoring against a forced opening.
- **Alert-2-Close** warning system provides audible and visual warnings when the garage door is about to close when using MyQ Technology.
- **The Protector System®** has safety sensors that project a light beam across the garage door opening, automatically reversing the door if anything interrupts the beam.

Included Accessories:



3-Button Remote Control (893LM)

Allows you to control up to three garage door openers, gate operators or MyQ Light Accessories.



Multi-Function Control Panel® (882LM)

Enables you to turn garage door opener lights on and off from inside the garage.

Optional Accessories:



Internet Gateway (828LM)

Connect your MyQ-Enabled Garage Door Opener and Accessories to the Internet with this device.



Ceiling Mount (195LM)

Give your garage the style it's been missing by hiding the wires and cords with this sleek ceiling mount. Works in most standard garages.



Remote Light Control (825LM)

Allows you to control any lamp with your garage door opener remote control or smartphone via the Internet Gateway and the free MyQ app.



Door and Gate Monitor (829LM)

Enables you to monitor and close up to four garage doors or gates from any room in your house.

SPEC SHEET STANDARD SPECIFICATIONS

DIMENSIONS

Installed Length: 128"
Maximum Door Opening: 7' 6" *
Headroom Clearance Required: 2"
*Up to 10' with optional 8' or 10' rails

CARTONS

Number of Cartons: 2
Carton 1: Dimensions and Contents:
- 20" x 12" x 10"
- 882LM Multi-Function Control Panel
- 893LM 3-Button Remote Control
- Garage Door Opener Head
- The Protector System® Safety Reversing Sensors
Carton 2: Dimensions and Contents:
- 10' 4" x 5" x 5"
- Assembled Solid-Steel T-Rail (Belt)

SECURITY+ 2.0® RADIO CONTROLS

Coding System: Smart Receiver Code Button and Indicator Light
893LM 3-Button Remote Control
Operating Range: 200' (approximately)
Operating Temperature: -40°F to 150°F
Frequency:
- Remote Control: 310, 315 & 390 MHz Tri-Band
- Receiver: Frequency Agile on 310, 315 & 390 MHz
Security+ 2.0 Anti-Burglary Coding

MyQ® RADIO

902-928 MHz
50 Channel FHSS (Frequency Hopping Spread Spectrum)
Provides two-way communication from garage door opener and MyQ Accessories.
Enables remote closing of garage door with key MyQ Accessories.
Enables monitoring and control of garage door openers and lighting controls via computer, tablet or smartphone.*
*Requires Internet Gateway Accessory Model 828LM

SECURITY+ 2.0 ENCRYPTED CONTROLS

882LM Multi-Function Control Panel
- Program Remote Controls
- Maintenance Alert System

CONVENIENCE / SAFETY

The Protector System Safety Reversing Sensors
Alert-2-Close Unattended Close Operation w/ Select Accessories*
Emergency/Quick Release
Automatic Trolley Reconnect
Ventilation /Pet Opening
Down Safety Reverse
Up Safety Stop
Door Open/Beam Obstructed/Lights On
Maintenance Alert System
PosiLock® secure lock system
*Timer-to-close feature requires purchase of 880LM or 881LM control panel and is for sectional doors only, not one piece doors.
*Unattended Operation functionality cannot be utilized when opener is installed on a one-piece door.

ELECTRICAL SPECIFICATIONS

POWER

Voltage: 120V AC, 60Hz
Current Rating: 4.5A
UL Listings: Yes
Length of Line Cord: 4' (3-prong)

ENERGY EFFICIENCY

Approximately 1 Watt Power In Standby Mode*
Enhanced CFL (Compact Fluorescent) Compatible
*Standby Mode at down limit, work lights off

LOGIC TYPE

Solid State Microcontroller with Built-in Surge Suppressor

LIGHTING

Number of Bulbs: 2
Maximum Wattage: 100 x 2
Adjustable Time, Solid-State Delay
Enhanced CFL (Compact Fluorescent) Compatible, Max 26 Watts

MECHANICAL SPECIFICATIONS

MOTOR

Horsepower: 1/2
RPM: 1,625
Thermal Protection: Automatic
Lubrication: Permanent

DRIVE MECHANISM

Drive Means: Full Reinforced Drive Belt
Reduction Means: Gear 16:1
Door Linkage: Adjustable Door Arm

ADJUSTMENTS

Auto Force
Electronic Limit Settings

TRAVEL RATE

Approximately 7" per second

SHIPPING WEIGHTS

Head: 24 lbs
Rail: 17 lbs.

MATERIALS

Chassis and Chassis Cover: Steel
Rail: Solid-Steel T
Trolley: Steel

WARRANTY

Lifetime Motor Warranty
Lifetime Belt Warranty
1 Year Parts and Accessories Warranty

HOMELINK® Compatible (version 4.0 or higher)*

*May require an external adapter depending on the model and year of your vehicle.
Visit homelink.com for additional information.

Note: To reduce the risk of injury to persons, when the Internet Gateway is used with garage door openers, the operator must be installed with sectional doors.

Churchill

Three-section carriage house
Steel garage doors

ASSA ABLOY

ASSA ABLOY Entrance Systems

The global leader in
door opening solutions



Authentic styling meets modern convenience

Key Benefits



Safety

When nothing but a true carriage house design will do, yet you still want the benefits of strength, durability and low maintenance, this is the door for you. With three sections instead of the usual four, ASSA ABLOY Churchill classic carriage house doors give you a more genuine look along with up-dated features like pinch protection, energy efficient options and the endurance of steel. It's the perfect marriage of timeless design and state-of-the-art performance.

- Seven classic carriage house designs
- Nine solid color options and multiple two-tone paint combinations
- Three dual-directional woodgrain finishes offer a more realistic look
- Three insulation choices – single, double and triple layer construction
- A selection of window designs and decorative hardware complete the authentic look

DECORATIVE HARDWARE
ALUMINUM



VERSAILLES
**Hinges with clavos
not recommended for arched openings*

CANTERBURY
*** Available for Monterey and Nantucket designs only.
Price upcharge for pre-drilled holes.*



STAMPED STEEL



BLUE RIDGE

ALPINE

LOCK
*Available on
Traditional
style doors*

ABS VINYL



CASTLE ROCK

MAPLE CREEK

